



Sig Sauer P320
Extended Magazine Release
Instructions



What is included:

- Sig Sauer P320 Extended Magazine Release.
- 15% Extra Power Magazine Release Spring.
- Allen Key for Disassembly.

Step 1: Clear Firearm

Remove the magazine and check the chamber, magazine well, and breech face for any ammunition.



Step 2: Disassemble Factory Magazine Release

Constantly depress the magazine release while performing this step. Insert the tip of the Allen key through the hole in the factory magazine release until it contacts the plastic magazine detent. Take care to avoid contact between the Allen key and the grip module to prevent cosmetic damage.



Step 2 Continued

Release the detent by performing a series of prying movements, moving up and down while pressing into the magazine release detent. Avoid contact between the Allen Key and the grip module. Once the detent protrudes past the surface, remove the Allen key. The magazine release, detent, and spring will then fall into the magazine well.



Step 3: Install the Extended Magazine Release

Insert the MCARBO magazine release and the stiffer spring (customer preference) through the right side for right-handed shooters, or through the left side for left-handed shooters.



Step 3 Continued

Push the magazine release through both holes of the grip module. Then, assemble the magazine release detent by pressing it into its seat until you hear an audible click. The extended magazine release has now been successfully assembled.



Step 4: Magazine Release Function Check

Using an empty magazine, test the functionality of the release. Insert the magazine into the well until it locks in place. Press the magazine release to eject the magazine. The force required to release the magazine can be adjusted to customer preference by choosing between the OEM spring, which is lighter, and the MCARBO spring, which is 15% heavier.



You must be 18 yrs of age to purchase. We advise that all parts purchased from our inventory be installed and inspected by a qualified gunsmith. Modifying your weapon may be prohibited in your state. Do not modify your sear or hammer engagement surfaces. Before installing please be sure to check all local state and federal laws. By installing this part you agree to take full responsibility for any and all legal, health and warranty consequences that may be incurred.

(P.) (727)223-1816 (E.) Help@Mcarbo.com